

COLOUR VIDEO DOOR ENTRY SYSTEM FOR VILLAS AND APARTMENTS



General Description

The Colour Video monitor is a Combined surface mounted Audio/Video Hands Free unit. Low profile, with crystal clear TFT picture quality. Dual tone chime, with 'Door Unlock', and 'camera self activate' function built in as standard. Four units can be connected in parallel within the one house so that when a call is activated all will sound together. There is also a 'Call' function in-built which allows them to be used as an intercom system.

The Door entry unit is a single call vandal resistant; surface mounted video entrance panel, which has built in speech unit, camera, and L.E.D illumination for poor light conditions. Suitable for internal/external uses.

CM-06DNRV3 LCD Colour Monitor

Working voltage:DC 18V±10%

Static Current:<60mA

Working current: 700mA

Colour display:3.5' TFT colour LCD display

Resolution:450X250 points.

Environmental Temperature:-10 to +55 degrees.

Humidity:45% to 95%

Dimension:185x120x28 mm

CE Approved

CM-06DNS7

Vandal Resistant Door Entry Unit

Working voltage:DC 12V±10%

Static current:≤12mA

Working current:≤180mA

Camera:1/3' CCD/CMOS

Viewing angel:92.8°

Min.luminance=0.1 Lux
Lens:F=3.6

Environmental Temperature:-25 to +70 degrees

Humidity:45% to 95%

Dimension:58x133x48 mm

CE Approved